

FOR POOLS up to **110m³** | EFFICIENCY | **Amazing prize!** | **7 versions available**

SILVERLINE



SILVERLINE

Efficiency at an amazing prize!

- High performance compressor
- Ultra silent & economical
- Anti-corrosion / Anti-UV Metal casing
- Twisted Tech Titanium heat exchanger

HEAT PUMP WARRANTY SERVICES AND PARTS

2 ANS


COMPRESSEUR GARANTI

5 ANS

SERPENTIN EN TITANE GARANTI CONTRE LA CORROSION

15 ANS

	55	70	90	120	150	180	220
Swimming pool volume	20-30m ³	30-40m ³	40-50m ³	45-65m ³	65-75m ³	70-90m ³	80-110m ³
COP air 26°C /water 26°C	6.13	6.21	6.17	6.22	6.20	6.20	6.19
Noise level at 10 m (db(a))	<30	<36	<37	<38	<39	<40	<40



POOLEX SILVERLINE		55	70	90	120	150	180	220	
Swimming pool volume		20-30m ³	30-40m ³	40-50m ³	45-65m ³	65-75m ³	70-90m ³	80-110m ³	
Reference		PC-SLP055	PC-SLP070	PC-SLP090	PC-SLP120	PC-SLP150	PC-SILVERPRO-180	PC-SILVERPRO-220	
Air 26°C Water 26°C Hygro 80%	Capacity (kW)	5.39	7.02	9.31	12.5	15.24	17.92	21.72	
	Power consumption (kW)	0.88	1.13	1.51	2.01	2.46	2.89	3.51	
	COP	6.13	6.21	6.17	6.22	6.2	6.2	6.19	
Air 15°C Water 26°C Hygro 70%	Capacity (kW)	3.9	5.07	7.05	9.05	10.59	12.6	15.3	
	Power consumption (kW)	0.81	1.01	1.39	1.78	2.07	2.47	2.98	
	COP	4.84	5.02	5.07	5.08	5.12	5.1	5.13	
Electricity supply		Mono 230V / 50Hz							
Max Power (kW)		1.29	1.83	2.51	3.03	3.58	4.43	5.46	
Max Current (A)		6.26	8.85	11.52	14.5	16.41	19.65	24.22	
Heating temperature range		15°C / 40°C							
Operating range		5°C / 43°C							
Flow (m ³ /h)		1.86	2.5	3.2	4.01	4.7	5.6	7	
Refrigerant		R32					R410A		
Packaging dimensions (mm)		845x330x610	905x350x645	1005x350x750				1150x425x820	
Dimensions (mm)		765x310x490	827x340x531	927x340x636				1067x405x692	
Net / Gross weight (kg)		39 / 44	41 / 50	49 / 59	42 / 62	54 / 64	62 / 72	62 / 72	
Noise level at 1 m (dB(A))		<46	<46	<47	<48	<49	<51	<51	
Noise level at 4 m (dB(A))		<39	<40	<42	<43	<45	<46	<46	
Noise level at 10 m (dB(A))		<30	<36	<37	<38	<39	<40	<40	
Compressor type		Rotary							
Compressor brand		Toshiba							
Heat exchanger		Twisted Tech® Titanium							
Function		Heating							
Load losses (mCE)		0.9	0.9	1	1.10	1.13	1.15	nc	

E.U. STANDARD TÜV CERTIFIED
Data provided for information purposes only. Can be subject to change without notice.

Poollex Silverline: The best compromise between efficiency and prize.







A high-performance Mitsubishi compressor and a new titanium double-spiral heat-exchanger give it a COP above 6, based on 26/26 conditions*.

Simple to use, the Poollex Silverline has an LCD control panel that can be remotely positioned at up to 10m and includes Touch & Go technology.

Available in 7 output ratings from 5.5 to 22 kW, it is suitable for pools up to 110 m³.

Poollex performance at the lowest price.

The POOLEX + : all accessories included

					
Delivered on wooden pallet	Anti-vibration support kit	Ø 50mm 1" 1/2 Connectors PVC	Wired control extension (10m)	Condensation drainage pipe	Maintenance kit Including multi-language usermanual

